



◆ SPECIFICATION

Model NO.	IPB-32812VW
Video Output Mode	POE Network
<b>Camera</b>	
Image Sensor	IMX124
Main Processor	HI3516D
Image Resolution	3.2MP
Effective Pixels	2065(H)*1153(V)
Compression	H.265/H.264/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/100000 Sec.; NTSC 1/1-1/100000 Sec.
S/N Ratio	≥52dB
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	Board Lens 2.8-12mm
Focus Control	Manual
Lens Type	Manual
Pixels	5M Pixels
<b>Night Vision</b>	
Infrared LED	42μ x 6PCS
Infrared Distance	90M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100 Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, TRCP, NTP, SMTP
ONVIF	Support ONVIF 2.4

P2P	YES, Support QR Code
POE	YES, Support IEEE 802.3af
WIFI	NO
Video Delay	0.3S (Within the Lan)
Main Stream 1	<a href="#">2048*1536@30fps</a>
Main Stream 2	<a href="#">1920*1080@30fps</a>
Sub Stream 1	<a href="#">720*480@30fps</a>
Tri Stream	<a href="#">352*288@30fps</a>
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

## Camera Features

Day/Night	Color / B&W (IR-CUT)
Image Config.	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	Yes, WDR
Recording Mode	NVR/NAS/CMS/Web
OSD Menu Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands

## General

Housing	Metal, IP66
Anti-cut Bracket	YES, Anti-Cut Bracket
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	260(W) x 98(H) X 95(D)mm
Weight	1.7kg