



◆ SPECIFICATION

Model NO.	IPB-A22812VW
Video Output Mode	POE Network
Camera	
Image Sensor	IMX290
Main Processor	HI3516D
Image Resolution	1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.265/H.264/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/100000 Sec.; NTSC 1/1-1/100000 Sec.
S/N Ratio	≥52dB
Scanning System	Progressive Scan
Lens	
Focus Length	Board Lens 2.8-12mm
Focus Control	Auto
Lens Type	Auto
Pixels	3M Pixels
Night Vision	
Infrared LED	42μ x 6PCS
Infrared Distance	90M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, TRCP, NTP, SMTP
ONVIF	Support ONVIF 2.4

P2P	YES, Support QR Code
POE	YES, Support IEEE 802.3af
WIFI	NO
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Sub Stream 1	720*480@30fps
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

Camera Features

Day/Night	Color / B&W (IR-CUT)
Image Config.	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	Yes, WDR
Recording Mode	NVR/NAS/CMS/Web
OSD Menu Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands

General

Housing	Metal, IP66
Anti-cut Bracket	YES, Anti-Cut Bracket
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	260(W) x 98(H) X 95(D)mm
Weight	1.7kg