



◆ SPECIFICATION

Model NO.	IP-360
Camera	
Image Sensor	IMX178
Main Processor	S2E66
Image Resolution	6MP
Effective Pixels	3096(H)*2080(V)
Compression	H.264/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter	Auto: PAL 1/25-1/10000 Sec; NTSC 1/25-1/10000 Sec
S/N Ratio	≥52dB
Scanning System	Progressive Scan
Audio	2-way audio
Alarm	1 Channel Input/Output
SD Card	Support 128GB Micro SD
Video Output	Poe Network/CVBS
Lens	
Focus Length	Board Lens 1.3mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5M Pixels
Night Vision	
Infrared LED	42μ x 3PCS
Infrared Distance	20M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100 Base-T)

Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, TRCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	Yes, Support QR Code
POE	Internal, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the lan)
Stream	Mode 1: Fisheye + Panorama + 3*PTZ 15fps@(1280x1280), 15fps@(2048x1536), 15fps@(1024x768)*3
	Mode 2: Fisheye or 4*PTZ 30fps@(3072x2048), 30fps@(1024x768)*4
	Mode 3: fisheye Main Stream+fisheye substream+3 PTZ 15fps@(1280x1280), 15fps@(720x720), 15fps@(1024x768)*3
	Mode 4: Panorama main stream+Panorama sub stream 15fps@2048x1536, 15fps@(704x576)
Max Resolution	3072 x 2048
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

Camera Features

Day/Night	Color / B&W (IR-Cut)
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)
Corridor Pattern	N/A
Defog Mode	Support
Motion Detection	Support
Privacy Macking	3 Rectangular Zone
WDR	Support
Recording Mode	NVR/NAS/CMS/WEB
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherland

General

Housing	Body: Metal, Bracket: Plastic
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	ϕ 120 x49(H) mm
Weight	500g